

LIGHT LIQUID SEPARATOR ECODEPUR[®] DEPUROIL[®] BY-PASS

TECHNICAL INFORMATION

ECODEPUR[®] DEPUROIL[®] is Light Liquid Separator destined to clean water polluted with light free floating liquids such as engine oils, gas, oil etc, Class 1 in accordance of EN 858, with double coalescent cell and automatic closure device.



ECODEPUR[®] DEPUROIL[®] Separators has CE marking, in accordance with the legal obligations that stems from the entry into force of the Regulation (UE) N.º 305/2011 of Construction Products, fulfilling all the requisites of the European Standard EN 858-1:2002.

EUROPEAN STANDARD	EN 858-1
EQUIPMENT IDENTIFICATION	Light Liquid Separator
MARCA	ECODEPUR [®]
CLASS EN 858-1	Class 1 (<5,0 mg "Mineral Oils"/l ⁽¹⁾)
COALESCENT CELL	Double (lamellar/fibrillar)
AUTOMATIC CLOSURE DEVICE	Included (system always calibrated)
FIRE CLASS REACTION	F
MATERIAL	Polyethylene
VENTE POINT	Included (1 ^{1/2} "
COVER	Included
SAMPLE BOX	Included

⁽¹⁾ Teste conditions EN 858-1 ⁽²⁾ DEPUROIL NS1,5 - Fibrillar

MODEL	NS (l/s)	MAXIMUM FLOW (l/s) with EXTERNAL BY-PASS				
DEPUROIL [®] NS 1,5	1,5	9	17	31	56	104
DEPUROIL [®] NS 3	3,0	9	17	31	56	104
DEPUROIL [®] NS 6	6,0	-	17	31	56	104
DEPUROIL [®] NS 8	8,0	-	-	31	56	104
DEPUROIL [®] NS 10/12	10,0/12,0	-	-	31	56	104
DEPUROIL [®] NS 15	15,0	-	-	-	56	104

Rev.1_02.03.16 | The pictures and dimensions can be changed without notice.